




## PRO SERIES

## EMBOSSER 2000



### FEATURES

standard



optional



### USED BY

Banks/Credit Institutions  
Insurance Companies  
Casino  
Clubs/Associations  
Government Offices  
Department Stores  
Service Bureaus


### IDEAL FOR

Credit cards and other  
Financial cards\*  
Gift cards  
ID cards  
Prepaid cards  
\* compatible with most 3rd party  
EMV personalization software  
solutions

### IN LINE SOLUTIONS

MULTIFEEDER 6000  
THERMAL 1000/2000  
INSERTER 3000  
LABEL DISPENSER 1500

### SOFTWARE



### INCLUDED

### HIGH SPEED CARD EMBOSSING

### THE FASTEST AND HEAVY DUTY PERFORMANCE



210-character capacity drum  
One pass front and rear infill (optional)  
Encoding:  
- Magnetic encoding and chip contact station (JIS/ISO)  
- Regular VISA + VISA mini card personalization (paired)




## PRO SERIES

## EMBOSSER 2000

### SPECIFICATIONS



**input hopper** 200 cards  
**output hopper** 200 cards  
**reject hopper** 10 cards capacity



**card format** CR80 - ISO standard  
**card thickness** ISO 7810 0,76 mm  $\pm$  0,08 / 30 mil  $\pm$  3  
**card materials** ABS, PVC and composite; semi transparent (available on request)

**internal tipper unit** Off-line tipping option (76 x 41 mm area / 3 x 1.61 in). Ribbon saving function  
**embossing area** 9 lines x 31 characters (76 x 45 mm area / 3 x 1.77 in)  
**drum capacity** 2 x 105-character-drums

**embossing characters** Standard Gothic, OCR7B, country specific characters (optional)

**dual infill** Optional for drum2: front infill (available fonts OCRB1/B4 and others) or rear infill device (CVV2-OCRA1) for front/rear infilling in one pass.  
 Possibility to have only front/only rear pass

**performance** Approx. 800 CPH  
**magnetic encoding** Optional: 3 ISO 7811 tracks, LoCo, HiCo, JIS  
 Optional: regular VISA + VISA mini card (paired)

**chip contact station** Optional  
**contactless station** Available on request

**communication interface** RS232 serial port  
**power supply** 100 - 117 - 220 - 230 or 240 Volts - 50 or 60 Hz  
**operating environment** 5°C - 40°C / 41°F to 104°F  
**dimensions (WxDxH)** 1200 x 480 x 350 mm / 47.2" x 18.9" x 13.8" in  
**weight** 80 Kg / 177 lbs  
**floor stand** Optional (required for in-line operation)

**operating systems** Multicard 2006 operating with Windows 2000/XP  
**application program** User interface monitoring, card production control, automatic card remake option, pre-encoded card reading with complete processin operation, system status and help messages displayed on Personal Computer

**in-line configuration** The Pro Series units can operate in a stand alone or in-line configuration with 2 up to 5 equipments. The EMBOSSER 2000 can be connected to: MULTIFEEDER 6000, THERMAL 1000/2000, INSERTER 3000, LABEL DISPENSER 1500

**RELIABLE:** the EMBOSSER 2000 is part of a tried and tested CIM product range. It combines heavy duty performance with easy installation in any working environment. A step forward in complete and fast plastic card personalisation

**FAST:** with two embossing drums for a total of 210-character capacity and its integrated MSP (Multi Smart Processing) system the EMBOSSER 2000 can process up to 4 cards simultaneously

**VERSATILE:** embossing, infill and tipping with magnetic stripe and / or smart card management into one single operation. The EMBOSSER 2000 can be fitted with special embossing characters to personalize international credit cards, such as VISA and MasterCard (all country specific characters), and perform dual infill personalization of the front and back in one pass



**EMBOSSER 2000**



**ROHS**



### KARE SMARTECH PVT LTD.

# 7, 2nd Link Street, CIT Colony, (Opp. Isabel's Hospital),  
 Mylapore, Chennai - 600 004. Tamilnadu, India.  
 Phone : 91 - 44 - 40 123 123 (20 Lines),  
 Email : info@karesmartech.com, sales@karesmartech.com  
 www.karesmartech.com

